

**EXCLUSIVE Range — Solid bamboo flooring with exceptional density, 3 crossed layers**

13BOCO128

- Dimensions:** 13 x 128 x 1850 mm
- Coating:** Mass- colored, factory applied WOCA color oil layer - matt appearance
- Color:** Corfou
- Chamfer:** GO2
- Installation:** Glued: Yes  
Floating: No  
Floorheating: Yes if glued  
Use in bathroom: Yes if glued
- Wearing surface** +/- 3 mm
- Box :** Content: 8 planks/box (1.894 m<sup>2</sup>)  
Weight: 10.72 kg
- Maintenance :** cfr maintenance instructions



BRINELL HARDNESS	86.5 N/mm <sup>2</sup> - EN 1534 norm (Report CTIB 5229/2)
CONTRACTION COEFFICIENT	0,14% per % humidity variation
HUMIDITY DEGREE	10% at 20 °C and 65% relative humidity 8% at 20 °C and 50% relative humidity
DENSITY	1100 kg/m <sup>3</sup>
FIRE NORM	CFLS1 if glued pose
FORMALDEHYDE EMISSION	0,04 mg/ m <sup>2</sup> h - EN 717-2 norm (Report CTIB 5229/2)
THERMIC RESISTANCE	0,072 m <sup>2</sup> ·K/W - EN 12664 norm (Report CTIB 5229/2)
PCP CONTENT	Below detection limit (Report CTIB 5229/2)
VOC FREE	Below detection limit – EN 15052 norm

**Do not forget the accessories !**

